

# DEEP PRIMER

---

**Description:**

PROREND DEEP PRIMER is applied indoors and outdoors as essential base component in the composition of a durable PROREND render or wall paint system.

**Composition:**

High-quality, factory-composed primer on a base of solvent-free acrylate dispersion with additives for better adhesion and stabilising capacity.

**Characteristics:**

Instant solvent-free primer with deep penetrating and stabilising capacity.

**Use:**

PROREND DEEP PRIMER is applied on powdering and porous backgrounds. It is particularly used for renovation and strengthening of old, weak and powdering backgrounds.

**Colours:**

Transparent.

**Technical data:**

S.G: ~ 1.0 g/cm<sup>3</sup>  
pH-value: ~ 7 – 9

**Sitework:**

Scaffolding must be independently tied, to allow uninterrupted application. Any faults in the structure, particularly those which may lead to moisture penetration, must be rectified.

**Site Conditions:**

Do not apply in rain or when the substrate and/or the air temperature is below 5°C or above 30°C or, if exposure to these conditions is likely during setting and drying. When used internally, ventilation is required during the first few hours of drying.

**Substrate:**

PROREND DEEP PRIMER may be applied to any substrate with a dusty surface which is required to be bound for subsequent applications of PROREND renders.

**Preparation:**

Thoroughly remove old, dusty, dirty and loose plaster and paint layers. Remove grease and dirt with Strikolith Strikoclean.

**Application:**

Apply PROREND DEEP PRIMER undiluted with a block brush. Apply in two layers, wet on wet, on porous and sandy backgrounds. Treat strong suction backgrounds like cellular concrete and gypsum backgrounds with one layer of PROREND DEEP PRIMER. Drying time 24 hours. Clean brushes and tools with water directly after use.

**Curing / Drying:**

PROREND DEEP PRIMER will normally be surface dry within several hours and through dry within 24 hours depending on the substrate and drying conditions.

**Protection:**

Cover parts which do not have to be treated with PROREND DEEP PRIMER with paper and tape. Remove them directly after applying the primer. Do not apply if background and air temperature falls below 5°C or when frost is expected.

**Cleaning:**

All equipment must be cleaned immediately after use with water. Waste material should not be emptied into any drainage system.

**Coverage:**

Depending on the background ~ 0.4l/m<sup>2</sup>.

**Packaging:**

Plastic can of 10 litres.

**Storage:**

Can be kept for approx. 2 years if stored in cool and frost-free conditions.

**Health & Safety:**

Refer to material safety data sheet for full details of safety measures

**Technical Service:**

A Technical Advisory and Specification Service is available on request.

*\* Subject to alteration due to technical developments.*